



Specifications:

Weight (Avg):	37 oz/ly (859 g/m ²)
Thickness:	.034" (0.863 mm) average
Backing:	Drill
Packaging:	20 yd bolts

Performance:

Fire Safety:

- Class A ASTM-E84 (GRC)
- NFPA 101 Life Safety Code
- CAN/ULC S102

Features and Benefits:

- Maximum impact resistance
- Best in class scratch and wear layer
- Comparable to rigid panel performance
- Resistant to chemicals
- Ease of installation

Environmental and Health:

- Phthalate Free
- Health Product Declaration
- Meets State of Washington Bldg. Specification for Indoor Air Quality
- Meets California Section 01350 Indoor Air Quality Standard
- Aggressive manufacturing materials recovery and reuse program
- Printed with water-based inks
- Free of PBDE's (Brominated Flame Retardants)

USGBC LEED Support:

- Support LEED v4.1 criteria
- Materials and Resources; Building Product Disclosure and Optimization (includes Recycled Content; Construction Waste Management; HPD's)
- Indoor Environmental Quality: Low emitting materials

Moisture, Mold and Mildew:

Vinyl wall protection functions as a vapor barrier. If water or moisture becomes trapped between the wall protection and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wall protection products.

Visit VersaWallProtection.com for complete specifications, installation instructions, cleaning directions and warranty.



© VersaDesignedSurfaces

Patent Pending