

Specifications

Versa PVC-FREE Via Monte pattern meets or exceeds all Type II requirements of CCC-W-408A/D and W-101.

| | |
|------------------------|-----------------------------------|
| Specifications: | Performance: |
| Weight (Avg.): | 20 oz/ly (452 gr/m ²) |
| Content: | Olefin Composite |
| Width: | 52/54" (132/137 cm) |
| Backing: | Osnaburg |
| Installation: | Reverse hang / Random match |

Custom colors, widths and microventing are available.

Fire Safety:

- Class A - ASTM E-84 (GRC)
 - NFPA 101 Life Safety Code
 - CAN ULC/S102
 - EN13501 (B-S1-d0)
-

Environmental and Health:

- PVC-FREE
 - Phthalate Free
 - Health Product Declaration
 - Free of Antimicrobials
 - Meets State of Washington Building Specification for Indoor Air Quality
 - Meets California Section 01350 Indoor Air Quality Standard
 - Aggressive manufacturing materials recovery and reuse program
 - Highly cleanable water-based inks
 - Free of Antimony and Halogenated flame retardants
 - 20% Recycled Content
 - Prop 65 Compliant
-

USGBC LEED Support:

- Supports USGBC LEED v4.1 Criteria
 - Materials and Resources; Building Product Disclosure and Optimization (Includes Recycled Content; Construction Waste Management; HPD's)
 - Indoor Environmental Quality; Low emitting materials
-

Moisture, Mold and Mildew:

Versa evo® PVC-Free wallcoverings function as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use and installation of vapor barriers.

Warranty:

Versa PVC-FREE is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other Versa innovations, visit our website at versapvcfreewallcovering.com.



VERSA®
DESIGNED SURFACES