

Zenith

SPECIFICATIONS:

Description: Type II, W-101 (Fed. Spec. CCC-W-408A/D)

Weight: 20 oz/ly (452 gr/m²)

Width: 52/54" (132/137 cm)

Content: 100% Vinyl

Backing: Osnaburg

Installation: Reverse Hang / Random Match

Fire Safety: Class A - ASTM E84 (GRC), CAN/ULC S102, Euroclass EN13501 (B-s1, d0)

Refer to versawallcovering.com for complete specifications.

©Versa Designed Surfaces

PRODUCT USE ADVISORY This product is intended for use in buildings designed, monitored and regularly maintained to avoid moisture accumulation on or within walls, particularly in warm, humid climates. The features that make wallcovering cleanable and durable also render it low in permeability. Wallcovering should not be installed on walls that contain excessive moisture or are subject to moisture infiltration.

REDUCED ENVIRONMENTAL IMPACT:

- Health Product Declaration (HPD)
- Environmental Product Declaration (EPD)
- Free of Phthalates, Formaldehyde, Heavy Metals (RoHS), PBDEs (Brominated Flame Retardants)
- Prop 65 Compliant
- Meets California Section 01350 Indoor Air Quality Standard (Low VOC)
- Highly Cleanable Water-Based Inks
- ASSURE™ Surface Protection Available
- Versa Permavent® Microventing Available



A219-352 Obsidian